



## Braids Brushing Machine BB-1525

- Demerge braids for various of small out diameter cables
- The machine is protected with a safety cover
- Only adjust the rotary speed and width when change wire
- Compact mechanical structure, customizable as per customer requirements
- Cable inlet sensor control
- Outside wire guide tube positioning

# Braids Brushing

# Braids Brushing Machine BB-1525

## Application Area/Concept

BB-1525 is a braids & shields brushing machine, mainly used to demerge braids cable shields for multi-core wires, coaxial cables, etc. In the process of demerging braids & shields, the cables' own structure will not be damaged and its electrical properties will not be affected. This machine can demerge braids & shields's length up to 150mm, cables out diameter up to 25mm. It is suitable for demerge braids & shields of different sizes and densities. Especially, it's very important to demerge for the new energy automotive wire harness's braids & shields. The machine operation is simple and safe, easy to produce.

## Function

- Mainly used to demerge braids cable shields
- Cables out diameter up to 25mm
- Simple adjust the rotary speed, be suitable for different cable types
- Simple adjust the belt brush width, be suitable for different cable types
- Simple and quick for the interchangeable belt brush
- Used for batch production
- Operation is simple and safe, easy to produce.



Before



After

## Technical Specifications

Cable Diameter	Up to 25 mm
Braids Length	Up to 150 mm
Rotary Speed	Adjust
Rotary Speed Range	0~1500r/m
Width Adjust Range	0~25mm
Production Rate	350~400Pcs/hour (depend on wire braids and operator)
Belt Brusher	Two
Drive Mode	Electric
Operating Mode	Sensor/Footpedal
Air Supply	No need
Power Supply	110/220 VAC , +/- 10%, 50-60 Hz; 600VA
Noise	< 75 dBA
Dimensions(LxWxH)	376x358x211mm
Weight	18 Kg
Important Notice	Chowho company recommends that wire samples be submitted in case where there is doubt as to the processing capabilities of a particular machine.

